

Technical Data Sheet

Product #HM-160

Application: Case and carton sealing/tray forming
General Info: HM-160 was formulated for high speed packaging applications. This product exhibits an aggressive tack which is important where short compression sections are encountered & excellent balance of heat and cold resistance.

Recommended Application Temp.: 350°F

Specification:
Color: Light Straw – Gardner
Color 4
Viscosity: 1,000 cps @ 350°F
Speed of Set: Fast
Open Time: Short
Softening Point: 225°F
Tack: Aggressive

Packaging: Slats, 50 lb. Boxes, 30 boxes per skid or bulk super sacks (approx. 1,500 lbs)

*Note: components contained in this product conform to FDA regulations 21 CFR 175.105 concerned with food packaging materials.

**Note: The date presented is based upon tests believed to be reliable. However, manufacturer does not guarantee its accuracy or completeness. Manufacturer will assume no responsibility for results obtained or for incidental or consequential damages arising from the use of this data. Customer is responsible for determining suitability of this product for his needs.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. American Chemical, Inc. warrants that the product conforms with American Chemical, Inc. written specifications, and is free from defects. American Chemical, Inc. disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.

7/2008